



Sicad s.p.A.

Via Caduti della Liberazione, 57  
21040 Uboldo (VA) – Italia  
Tel: +39 02 964121 Fax: +39 02 96412294  
Web: www.eurocel.it

## PRODUCT INFORMATION

# EUROCEL 7490 BPA

### DESCRIPTION

Double sided clear PVC film coated with an acrylic adhesive.

### PRODUCT DATA

Backing	0.035 mm PVC film; transparent
Adhesive	Acrylic solvent based
Liner	White siliconized paper

	Unit	Value	Method
Total thickness (without Liner)	mm	0.215	PSTC 133
Adhesion to steel	N/25mm	Int: 19 – Ext: 19	PSTC 101
Tensile strength MD	N/25mm	140	PSTC 131
Elongation to break	%	75	PSTC 131
Temperature resistance	°C	70°C	=

### APPLICATION

Designed to permanently fix profiles, trims, displays, plates and decorative parts in many types of industries and areas (wood, furniture, plastics...). Thanks to its very high adhesive weight and adhesion level, it is suitable on rough surfaces. Very easy to use.

Features	Benefits	
Acrylic solvent based	<ul style="list-style-type: none"> <li>✓ Very high initial tack</li> <li>✓ Good ageing properties</li> </ul>	<ul style="list-style-type: none"> <li>✓ Versatility, high adhesion on most surfaces</li> <li>✓ Good resistance to plasticizers</li> </ul>
PVC transparent film	<ul style="list-style-type: none"> <li>✓ Provides high flexibility combined with high shear resistance</li> <li>✓ Conformable</li> </ul>	<ul style="list-style-type: none"> <li>✓ Invisible seal</li> <li>✓ Hand tearable in crush cut version</li> </ul>

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.