



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL MSK 6127

DESCRIPTION

Paper masking tape for decoration and painting jobs.

PRODUCT DATA

Backing	52 g/m ² saturated crepe paper; white
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.110	PSTC 133
Adhesion to steel	N/25mm	4	PSTC 101
Tensile strength MD	N/25mm	80	PSTC 131
Elongation at break	%	6	PSTC 131
Temp. Resistance	°C	60°C (30 min)	=

APPLICATION

General purpose masking tape for general use and simple jobs in the building, construction and industrial sectors. Recommended to remove within 30 hours.

Features	Benefits	
Natural rubber and resins solvent based adhesive	✓ Good adhesion on irregular surfaces	✓ Easy removal without adhesive residue
Saturated paper backing	✓ Well conformable to most shaped surfaces ✓ Hand tearable	✓ Compatible with most common paints and lacquers ✓ Removable without tearing

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

MK027EN_REV02_MSK6127

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.