



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL MSK 98

DESCRIPTION

Waterproof green masking tape.

PRODUCT DATA

Backing	63 g/m ² waterproof saturated crepe paper; green
Adhesive	Natural rubber and resins solvent based

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	4.8	PSTC 101
Tensile strength MD	N/25mm	90	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	90°C (30 min)	=

APPLICATION

Waterproof masking tape widely used for car repair applications as well as for wall-painting on building and construction sites and industrial use. Recommended to remove within 48 hours.

Features	Benefits	
Natural rubber and resins solvent based adhesive	<ul style="list-style-type: none"> ✓ Good adhesion on uneven surfaces also ✓ Heat resistant up to 90°C (30 min) 	<ul style="list-style-type: none"> ✓ Easy removal without adhesive residue, if it is removed as soon as paint is dry
Water resistant saturated paper backing	<ul style="list-style-type: none"> ✓ Well conformable to most shaped surfaces ✓ Highly resistant to moisture and water 	<ul style="list-style-type: none"> ✓ Compatible with most common paints and lacquers ✓ Removable without breaking ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

MK020EN_REV02_MSK98

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.